



OXYGEN METER, Model: DO-5510

FEATURES



- * This Digital Oxygen Meter is supplied with a polarographic type probe with an incorporated temp.' sensor which serves for precision Dissolved Oxygen (DO), Oxygen in air (O²), Temp. measurement Applications for Aquarium, Medical research, Agriculture, Fish hatcheries, Laboratory, Water conditioning, Mining industrial, Schools & Colleges, Quality control.
- * Automatic temp. compensation from 0 to 50 °C for sensor.
- * Build in "% SALT" & "Mountain Height" compensation, adjust the factor by push the button on the front panel.
- * Auto shut off saves battery life.
- * Microprocessor circuit assures high accuracy and provides special functions and features.
- * Super large LCD display with contrast adjustment for best viewing angle.
- * Multi display, show oxygen & temp. at the same time.
- * Records Maximum, Minimum and Average readings with RECALL.
- * Data hold.
- * Operates from 006P DC 9V battery.
- * RS 232 PC serial interface.
- * Build in temperature °C, °F measurement.
- * Used the durable, long-lasting components, including a heavy duty & compact ABS-plastic housing case.

SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.		Operating Temperature	0 °C to 50 °C (32 °F to 122 °F)
Display	*13 mm(0.5"). Super large LCD display with contrast adjustment for best viewing angle. *Dual function meter's display.		Operating Humidity	Max. 80% RH.
			Sample Time	Approx. 0.4 sec.
Measurement & Range	Dissolved Oxygen	0 to 20.0 mg/L	Power Supply	006P DC 9V battery (Heavy duty type).
	Oxygen in Air	0 to 100.0 %	Power Current	Approx. DC 6.6 mA.
	Temperature, °C	0 - 50 °C	Weight	335 g/0.74 LB
	Temperature, °F	32 - 140 °F	Size	Main instrument: 180 x 72 x 32 mm. (7.1 x 2.8 x 1.3 inch)
Resolution	Dissolved Oxygen	0.1mg/L		Oxygen probe: 125 mm x 20 mm Dia. (4.9" x 0.8" Dia.)
	Oxygen in Air	0.1% O ²	Accessories included	Oxygen probe 1 PC.
	Temperature	0.1 °C.		Carrying case 1 PC.
Accuracy (23 ± 5 °C)	Dissolved Oxygen	+0.4mg/L.	Operation manual	1 PC.
	Oxygen in Air	+ 0.7% O ²	Spare Diaphragm (5 PCs per pack)	OXDP-02 1 set
	Temperature	+ 0.8 °C/1.5 °F	Probe-filling Electrolyte	OXEL-03 1 set
Sensor Structure	The polarographic type oxygen probe with an incorporated temp. sensor.		Optional Accessories	Oxygen probe (for DO-5510)
Probe Compensation & Adj.	Temperature	0 to 50 °C. Automatic	OXPB-01C
	Salt	0 to 39 % Salt		Spare Diaphragm (5 PCs per pack)
	Height (M. T.)	0 to 3900 meterOXDP-02	
Memory Recall	Records Maximum, Minimum and Average readings with RECALL.		Probe-filling ElectrolyteOXEL-03
Power off	Auto shut off saves battery life, or manual off by push button.			
Data Output	RS 232 PC serial interface.			
Over input indication	Indication of "----"			

Clean Rooms | Pharma | Hospital | HVAC | BulkDrugs | Chemicals | Heavy Machinery
Hydraulics & Vacuum Industry | Green House | Server Room | Confined Space | Cold Storage

Instrukart Holdings

India Toll Free : 1800-121-0506 | Ph : +91 (40)40262020

Mob +91 7331110506 | Email : info@instrukart.com

#18, Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.

