

WIND SPEED • MAXIMUM WIND SPEED • AVERAGE WIND SPEED

Know your conditions

Measure environmental conditions quickly and accurately

Wide range of wind speeds and a low start-up speed

Reliable, portable and easy to use

- Small, robust design
- Data hold function
- Large easy to read display
- Waterproof and floats
- High precision jewel mounted impeller
- Replaceable impeller assembly
- Long life lithium battery
- Low cost
- Includes protective cover, lanyard and battery
- 5 year warranty
- Choice of measurement units: Knots, Metres per second, Kilometres per hour, Miles per hour, Feet per minute and Beaufort Force



Measurement

Current, Max and Average
Wind speed

Units of Measure

knots, m/s, km/h, mph,
ft/min, Beaufort (B)

Accuracy

±3% of reading
or ±0.1 m/s

Range

0.4 to 40 m/s

DESCRIPTION

The Kestrel 1000 pocket anemometer is the first and entry level of the Kestrel range, providing the user with accurate wind speed readings. It has three buttons below the display, making operation simple and allowing the user to view data in current, maximum or average displays, the buttons also allow operation of the data hold function.

The Kestrel 1000 is a small electronic rotating vane type anemometer, easily carried in a pocket. It uses high precision jewel bearings and a light weight impeller to provide accurate air flow measurements even at low speeds. The impeller assembly can be replaced by the user if damaged.

Low power microprocessor technology is used to provide speed, maximum speed, average speed and units selection; functions normally only found on more expensive instruments. The liquid crystal display has large 9mm high digits for a clear readout.

Power is from an easily replaceable standard lithium coin cell battery, which will typically give up to 300 hours of operation. The instrument automatically switches off if no keys are pressed for 45 minutes.

The Kestrel 1000 is made from high impact injection moulded plastic and corrosion resistant materials with the electronics fully sealed. It will float if accidentally dropped into water. There is a hard cover for protection when not in use and a lanyard is provided for added security.

All Kestrels have a 5 year warranty.

APPLICATIONS

Agriculture – checking conditions prior to crop spraying or burning

Aviation – gliders, para-gliders, micro-lights, parachutists and ballooning

Construction – site safety, working conditions, working at height in cranes or access vehicles

Education – air flow experiments, environmental studies, outdoor sports

Heating and ventilation – air flow through fans, checking condition of filters

Industry – air flow measurements, pollution control
Science – aerodynamics, environmental science and meteorology

Fire fighters – checking fire spreading hazard

ALL - sailors, walkers, model boats/air craft, kite flyers, archery, shooting, fishing, golf & athletics

Kestrel® 1000 POCKET ANEMOMETER

SPECIFICATION



Physical	Dimensions		122mm x 42mm x 20mm
	Cover dimensions		122mm x 46mm x 26mm
	Weight		65g
	Cover weight		37g
	Lanyard		0.5m
	Case colour		Blue
Display	Display type		Reflective 3½ digit LCD.
	Digit height		9mm
	Display update		1 second
	Functions	Current wind speed (3 second average)	
		Average speed since power on (AVG)	
		Maximum 3 second gust since power on (MAX)	
		Data hold (HOLD)	
Performance	Speed units		kt, m/s, km/h, mph, ft/min, Beaufort Force (B)
	Speed (1 sec response)	Operational range	0.4m/s to 60m/s (0.8 to 135.0mph)
		Specification range	0.4m/s to 40m/s (0.8 to 89.0mph)
		On axis accuracy	Larger of ± 3% of reading or least significant digit. (Some loss of accuracy from bearing wear may occur with sustained operation at or near maximum speed)
		Off-axis response	-1% @ 5°, -2% @ 10°, -3% at 15°
		Calibration drift	<1% after 100hrs operation at 7m/s
		Resolution	0.1 kt, m/s, km/h, mph. 1 FPM below 1999 FPM, 10 FPM above 2000 FPM. 1 Beaufort (0 to 12)
Sensor	Impeller		Diameter 25mm. High precision axle and jewel (sapphire) bearings. User replaceable impeller assembly
	Sealing		Electronics enclosure IP67 [Water resistant]
Environmental	Shock		Drop tested (MIL-STD.810F - unit only)
	Temperature		Operating range: -10°C to +55°C (for LCD readability and batteries) Storage range: -30°C to +60°C
	EMC		CE marked
	Battery		Lithium coin cell CR2032, included, user replaceable
Miscellaneous	Battery Life		300 hours of use, typical
	Auto switch off		45 minutes after last key press
	Cover		Snap on hard cover for protection
	Certification		Wind speed measurements are tested during manufacture. A certificate of conformity (C of C) is included with each Kestrel. A calibration certificate is available for an additional fee.
	Guarantee		5 years

The manufacturer reserves the right to amend the specification and therefore the information in this document may be subject to change. Please check our website www.rpr.co.uk

