

# Non-contact voltage tester

testo 745

---

Filter for high-frequency interference signals

---

---

Adjustable sensitivity

---

---

Visual and acoustic signal

---

---

Waterproof and dustproof according to IP 67

---

---

Measuring point illumination

---



The testo 745 non-contact voltage tester with a voltage range of up to 1,000 V AC is particularly well-suited to fast initial checking of any suspected fault sources. When the presence of alternating current is determined, the testo 745 gives a warning via a clear visual and acoustic signal.

In order to increase reliability, the voltage tester has a filter for high-frequency interference signals and is also waterproof and dustproof according to IP 67.

## Technical data/accessories

### testo 745

testo 745, non-contact voltage tester  
including batteries

Order no. 0590 7450



### Technical data

Voltage testing	12 to 1,000 V AC
Measuring point illumination	✓
Measurement category	CAT IV 600 V CAT III 1,000 V
Protection class	IP 67
Operating temperature	-10 to +50 °C
Storage temperature	-15 to +60 °C
Dimensions	155 x 25 x 23 mm (L x W x H)
Weight	63 g
Authorizations	CSA, CE
Standards	EN 61326-1, EN 61010-1

1981 1514/msp/I/01.2018

### Accessories

### Order no.

ISO calibration certificate voltage tester	0520 0750	
DAkkS calibration certificate voltage tester	0520 0751	

Subject to change without notice.

