

Temperature measuring instrument (1-channel)

testo 926 - The allrounder in temperature measurement

- Ideally suited to applications in the food sector
- Wireless measurement with radio probes possible
- Audible alarm (adjustable limit values)
- TopSafe, the indestructible protective cover, protects from dirt and impact
- Min./max. value store
- Automatic recognition of final value (Auto-hold)
- Certified according to EN 13485



The testo 926 is an exact temperature measuring instrument which is particularly suited to applications in the food sector. In addition to the broad selection of classical probes with a cable, a wireless radio probe can also be connected if required. The dishwasher-safe TopSafe protects the instrument from dirt, water and impact.

As the user, you can store limit values in the instrument yourself; as soon as these upper and lower values are violated, an audible warning signal sounds. This alarm function and the automatic final value recognition simplify

measurement, and support you in recognizing and interpreting the measurement values correctly. In addition to this, the instrument reliably stores the minimum and maximum measurement values.

testo 926 conforms to HACCP as well as EN 13485.

This makes it the ideal partner for large kitchens, hotels, restaurants or in the food industry.

Technical data

testo 926

testo 926-1, 1 channel food temperature measuring instrument T/C Type T, audible alarm, connection to an optional radio probe, with battery and calibration protocol

Part no. 0560 9261



testo 926, Starter set

testo 926, Starter set, 1 channel food temperature measuring instrument T/C Type T, incl. TopSafe, standard immersion/penetration probes, battery and calibration protocol

Part no. 0563 9262

Sensor type Type T (Cu-CuNi) or NTC and Type K if radio immersion/penetration probes are used

Measuring range	-50 to +400 °C
Accuracy ±1 digit	±0.3 °C (-20 to +70 °C) ±(0.7 °C ±0.5% of m.v.) (remaining range)
Resolution	0.1 °C (-50 to +199.9 °C) 1 °C (remaining range)

General technical data

Operating temperature	-20 to +50 °C
Storage temperature	-40 to +70 °C
Battery type	9V block battery, 6F22
Battery life	200 h (connected probe, backlight off) 45 h (radio mode, backlight off) 68 h (connected probe, backlight always on) 33 h (radio mode, backlight always on)
Dimensions	182 x 64 x 40 mm
Housing material	ABS
Weight	171 g
Standard	EN 13485



TopSafe, protection of the measuring instrument against impact, dirt and water, dishwasher-proof (optional)



Wireless measurement with radio probes possible (optional)



Measurement data printout on site on the Testo fast printer



Connection for external probes and charger

Accessories


Accessories for measuring instrument	Part no.
9V rech. battery for instrument, instead of battery	0515 0025
Radio module for upgrading measuring instrument with radio option	
Radio module for measuring instrument, 869.85 MHz, approval for the countries: DE, FR, UK, BE, NL, ES, IT, SE, AT, DK, FI, HU, CZ, PL, GR, CH, PT, SI, MT, CY, SK, LU, EE, LT, IE, LV, NO	0554 0188
Radio module for measuring instrument, 915.00 MHz FSK, approval for USA, CA, CL	0554 0190
Printer and Accessories	
Testo fast printer IrDA with wireless infrared interface; 1 roll thermal paper; 4 AA batteries	0554 0549
Spare thermal paper for printer (6 rolls), permanent ink measurement data documentation legible for up to 10 years	0554 0568
External fast charger for 1-4 AA rech. batteries, incl. 4 Ni-MH rech. batteries with individual cell charging and charge control display, incl. impulse trickle charging, integrated discharge function, with built-in international mains plug, 100-240 V, 300 mA, 50/60 Hz	0554 0610
Transport and Protection	
TopSafe, protects from impact and dirt	0516 0220
Service case for measuring instrument, probe and accessories, dimensions 454 x 316 x 111 mm	0516 1200
Service case for measuring instrument and probe, dimensions 454 x 316 x 111 mm	0516 1201
Case for measuring instrument and probes	0516 0191
Calibration Certificates	
ISO calibration certificate/temperature for air/immersion probes, calibration points -18°C; 0°C; +60°C	0520 0001
ISO calibration certificate/temperature for air/immersion probes, calibration point -18°C	0520 0061
ISO calibration certificate/temperature for air/immersion probes, calibration point 0°C	0520 0062
ISO calibration certificate/temperature for air/immersion probes, calibration point +60°C	0520 0063
ISO calibration certificate/temperature for air/immersion probes, calibration points -8°C; 0°C; +40°C	0520 0181
ISO calibration certificate/temperature meas. instr. with surface probe; calibration points +60°C; +120°C; +180°C	0520 0071
ISO calibration certificate/temperature single point calibration for surface thermometer; calibration point +60°C	0520 0072
ISO calibration certificate/temperature single point calibration for surface thermometer; calibration point +120°C	0520 0073

Radio probes

Radio handles with probe head for air-/ immersion-penetration-meas.

Part no.


Radio handle for plug-in probe heads, incl. T/C adapter, approval for the countries: DE, FR, UK, BE, NL, ES, IT, SE, AT, DK, FI, HU, CZ, PL, GR, CH, PT, SI, MT, CY, SK, LU, EE, LT, IE, LV, NO; Radio freq. 869.85 MHz FSK	0554 0189	
T/C probe head for air/immersion/penetration measurement (T/C Type K)	0602 0293	
Radio handle for plug-in probe heads, incl. T/C adapter, approval for USA, CA, CL; Radio freq. 915.00 MHz FSK	0554 0191	
T/C probe head for air/immersion/penetration measurement (T/C Type K)	0602 0293	

Dimensions Probe shaft/probe shaft tip	Measuring range	Accuracy	Resolution	t ₉₉
	-50 to +350 °C Short-term to +500 °C	Radio handle: ±(0.5 °C +0.3% of m.v.) (-40 to +500 °C) ±(0.7 °C +0.5% of m.v.) (remaining range) T/C probe head: Class 2	0.1 °C (-50 to +199.9 °C) 1.0 °C (remaining range)	t ₉₉ (in water) 10 s


Radio handles with probe head for surface measurement

Part no.

Radio handle for plug-in probe heads, incl. T/C adapter, approval for the countries: DE, FR, UK, BE, NL, ES, IT, SE, AT, DK, FI, HU, CZ, PL, GR, CH, PT, SI, MT, CY, SK, LU, EE, LT, IE, LV, NO; Radio freq. 869.85 MHz FSK	0554 0189	
T/C probe head for surface measurement (T/C Type K)	0602 0394	
Radio handle for plug-in probe heads, incl. T/C adapter, approval for USA, CA, CL; Radio freq. 915.00 MHz FSK	0554 0191	
T/C probe head for surface measurement (T/C Type K)	0602 0394	

Dimensions Probe shaft/probe shaft tip	Measuring range	Accuracy	Resolution	t ₉₉
	-50 to +350 °C Short-term to +500 °C	Radio handle: ±(0.5 °C +0.3% of m.v.) (-40 to +500 °C) ±(0.7 °C +0.5% of m.v.) (remaining range) T/C probe head: Class 2	0.1 °C (-50 to +199.9 °C) 1.0 °C (remaining range)	5 s

Radio probes

Radio handles for attachable T/C probes			Part no.
Radio handle for plug-in probe heads, incl. T/C adapter, approval for the countries: DE, FR, UK, BE, NL, ES, IT, SE, AT, DK, FI, HU, CZ, PL, GR, CH, PT, SI, MT, CY, SK, LU, EE, LT, IE, LV, NO ; Radio freq. 869.85 MHz FSK			0554 0189
Radio handle for plug-in probe heads, incl. T/C adapter, approval for USA, CA, CL; Radio freq. 915.00 MHz FSK			0554 0191
Illustration	Measuring range	Accuracy	Resolution
	-50 to +1000 °C	±(0.7 °C +0.3% of m.v.) (-40 to +900 °C) ±(0.9 °C +0.5% of m.v.) (remaining range)	0.1 °C (-50 to +199.9 °C) 1.0 °C (remaining range)

Technical data Radio probes

Radio immersion/penetration probe, NTC

Battery type	2 x 3V button cell (CR 2032)
Battery life	150 h (meas. rate 0.5 s) 2 months (meas. rate 10 s)









Radio handle

Battery type	2 AAA micro batteries
Battery life	215 h (meas. rate 0.5 s) 6 months (meas. rate 10 s)

Common Technical Data




Measuring rate	0.5 s or 10 s, adjustable on handle
Radio coverage	Up to 20 m (without obstructions)
Radio transmission	Unidirectional
Operating temperature	-20 to +50 °C
Storage temperature	-40 to +70 °C

Probes

Probe type	Dimensions Probe shaft/probe shaft tip	Measuring range	Accuracy	t ₉₉	Part no.
Food probes					
Robust food penetration probe with special handle, reinforced cable (PVC), T/C Type T, Fixed cable	 115 mm Ø 5 mm	30 mm Ø 3.5 mm	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	6 s 0603 2492
Frozen food probe, corkscrew design, T/C Type T, Plug-in cable	 110 mm Ø 8 mm	30 mm Ø 4 mm	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	8 s 0603 3292
Stainless steel food probe (IP67) with PUR cable, T/C Type T, Fixed cable	 110 mm Ø 4 mm	30 mm Ø 3.2 mm	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	7 s 0603 2192
Stainless steel food probe (IP67), with FEP cable to +200 °C, TC Type T, Fixed cable	 125 mm Ø 4 mm	30 mm Ø 3.2 mm	-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	7 s 0603 3392
Waterproof, super-quick needle probe for measurements without visible penetration hole, T/C Type T, Fixed cable	 150 mm Ø 1.4 mm		-50 to +250 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	2 s 0628 0027
Quick needle probe to monitor cooking in oven, T/C Type T, Fixed cable, Probe cable heat-proof up to +250 °C	 60 mm Ø 1.4 mm		-50 to +250 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	2 s 0628 0030
Measurement tip with T/C adapter Type T, ideal for fast-action measurement on incoming goods	 Ø 1.5 mm 500 mm		-50 to +350 °C	±1 °C (-40 to +133 °C) Class 2 (remaining range) ¹⁾	5 s 0628 0023
Flexible oven probe, Tmax +250 °C, PTFE cable	 2000 mm Ø 1.5 mm		-50 to +250 °C	Class 1 ¹⁾	0603 0646

1) According to standard EN 60584-2, the accuracy of Class 1 and Class 2 refers to -40 to +350 °C (Type T).

Probes

Probe type	Dimensions Probe shaft/probe shaft tip	Measuring range	Accuracy	t ₉₉	Part no.
Air probes					
Robust, affordable air probe, T/C Type T, Fixed cable 1.2 m		-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	25 s	0603 1793
Surface probes					
Waterproof surface probe with widened measurement tip for flat surfaces, T/C Type T, Fixed cable 1.2 m		-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	30 s	0603 1993
Immers./penetr. probes					
Waterproof standard immersion/penetration probe, T/C Type T, Fixed cable		-50 to +350 °C	±0.2 °C (-20 to +70 °C) Class 1 (remaining range) ¹⁾	7 s	0603 1293

¹⁾ According to standard EN 60584-2, the accuracy of Class 1 refers to -40 to +350 °C (Type T).

NDTKALA[®]
Non-Destructive Test (NDT) Equipment



تامین تجهیزات و مواد مصرفی تست های غیر مخرب ایران

۰۲۱-۷۱۰۵۳۸۸۸ | ۰۹۱۲۰۲۴۶۲۷۰