



YG60—60 Degree High Precision Gloss meter

YG60 60° precision gloss meter is independently developed by Shenzhen ThreeNH Technology Co., Ltd with independent intellectual property, manufactured according to international standard ISO2813 and China standard GB/T 9754. With auto-calibration and high-end QC software, it can meet the first grade requirements of JJG696.



Angle 60°(Accurate)



USB



QC Data Printing



QC Software



PRODUCT FEATURES

1. Elegant Design combined with aesthetics and ergonomics
2. With auto-calibration function
3. Meet the first grade requirements of JJG696
4. Large storage to save over 35000 data
5. Auto Power-off within optional 30-120 seconds
6. Comply to ISO2813,ASTM523, GB/T9754
7. With PC software for quality report, more extend functions
8. With multi working modes and multi-functions for most customers' requirements



APPLICATION INDUSTRY

YG60 60° Precise Gloss Meter , are widely used in paint, ink, stoving varnish, coating, wood products; marble, granite, vitrified polished tile, pottery brick and porcelain; plastic, paper; hardware industries, etc. for gloss measurement and gloss data transmission.



Automobile




Leather



Plastic




Metal



Stone material



Coating



Others

TECHNICAL SPECIFICATIONS

Measuring Angle: 60°
Measuring Range: 0-1000GU
Measuring Area: 9x15mm
Division Value: 0.1GU
Measuring Modes: Basic mode; Statistic mode; Continuous mode; QC mode
Measuring Time: 0.5S
Repeatability: 0~100GU : ±0.2GU; 100~2000GU : ±0.2%GU
Accurate: Conform with JJG696 first grade requirements of gloss meter
Auto Power-off Time: Within 30s-120s
Long-time Calibration: Automatically check and made the calibration
Language: Chinese & English
Storage: 35000(Basic mode & Statistic mode : 1500; Continuous mode : 10000; QC mode: 10000)
Display: 2.3 inch white and black screen
Size: 160*52*84mm
Weight: About 300g
Power Supply: 1pc dry-cell battery(can measure 10000 times) or use USB Charge
Interface: USB
PC Software: GQC6 QC software can printing testing report and with more extended functions
Operation Temperature Range: 0-40°C (32-104° F)
Storage Temperature Range: -20-50°C (-4-122° F)
Humidity Range: < 85% RH, without condensation
Standard Accessories: USB cable, user manual, calibration plate, QC software
Optional Accessories: Miniature printer
Notification: the technical parameter is only for reference



3nh[®]
Focus on Color

SHENZHEN ThreeNH TECHNOLOGY CO.,LTD.

Address:F/6, Block 5B, Skyworth Inno Valley, Tangtou 1st Road,
Shiyan, Baoan District, Shenzhen, P.R. China

Service Hotline: 400-666-2522

Email: 3nh@3nh.com

Tel: 86-0755-26508999

Fax: 86-0755-27190609