



Product Detail

Leeb Hardness Tester AL-150A

Share to: WeChat Sina Weibo QQ Qzone douban Baidu Tieba



by Amitteri design

Original: ¥0.00

Detail

Product Description

The Leeb Hardness Tester applicable for failure analysis of installed machinery or permanent parts of assembl of molds, heavy work pieces, pressure vessel, steam generator and other equipment, testing surface of a smal inspection of bearing and other mass produced parts on a production line ,material identification in the warehol materials and rapid testing in large range and multi-measuring areas for large-scale work piece. Surface Profile blasting industry, the printing industry, Spraying Anti Corrosion Industry, According to the selected measureme calculated from the corresponding parameters, in the liquid crystal display clearly shows all the measured para

Product Feature

- * Transform between HL/HRC/HRB/HB/HV/HS.
- * Store the latest 250 groups measurements.
- * Select measured material and way by key.
- * Can show measurements repeatedly to remove the large errors.
- * Use USB data output with connection PC.
- * Provide Bluetooth data output choice.

Product Parameters

Display error ±0.8% at LD=900
200~900 HLD
9 different common materials
-10°C~50°C
-30°C~60°C
≤90%
140x70x30 mm
2x1.5vAAA Um-4 Battery
130 g (Not including batteries)

Product Accessories

Standard Accessories	Main Unit
	Standard Test Block
	Measurement Sensor
	Small Support Ring
	Cleaning Brush
	Carrying Case
	Operation Manual
Optional Accessories	Impact Body
	Support Ring
	USB data output
	RS-232 data output
	Bluetooth™ data output

Buying Guide

When you choose the model number of Amittari instrument, the default is standard delivery. If you need other of please tell our customer -service worker.

Non-Destructive Test (NDT) Equipment

The following three items are basic optional accessories choices

Standard Accessories+USB data output

Standard Accessories+Bluetooth data output

Bluetooth Accessories

Amittari instruments generally can be supplied with Bluetooth data output function (except few instruments). output is included in optional accessories, not standard delivery, it needs to be indicated when choose 10 meter distance can be chosen. Please kindly contact with the customer-service worker if you need Bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker if you need bluetooth data output in the customer service worker in the customer service worke

HOME PRODUCTS ABOUT AM News NEWS/ARTICLES CONTACT US

©2013 广州安妙仪器有限公司 All rights reserved Guangdong ICP prepares 11086176-4 Mobile version | This website uses (FAISCO Build | Login | 粤ICP备11086176号