



EMC & LVD
EN : 61326
EN : 60825-1

Model: LDM- 60H

متر لیزری ۶۰ متری

قابلیت اندازه گیری :

محدوده اندازه گیری : 0.05 ~ 60 m

دقت اندازه گیری : ±1.5mm

دیگر قابلیت ها :

اندازه گیری حجم ، مساحت ، ارتفاع

امکان نمایش بر حسب متر ، اینچ ، فوت

چراغ پس زمینه نمایشگر

حافظه مینیمم / ماکزیمم مقادیر

حافظه داخلی جهت ۲۰ ثبت مقادیر اندازه گیری شده

همراه با کیف حمل



Specification	
Measuring Range	0.05 to 60 m / 0.15 ft to 196.8 ft
Measuring accuracy(2σ)	Typically: ± 1.5mm(0.06± in)
Smallest unit displayed	1mm
Measuring units	m,in,ft
Laser Class	Class II 635 nm, < 1mW
Dust Protect/Splash proof	IP 54
History measurement records	20
Keyboard Type	Super Soft-Touch (Long life)
Operating Temperature	- 10 °C to 50 °C (14 °F to 122 °F)
Storage Temperature	- 20 °C to 60 °C (- 4 °F to 140 °F)
Battery Life	Up to 4,000 measurements
Batteries	Type AAA 2 x 1.5V
Auto. laser switch-off	after 0.5 min
Auto instrument switch-off	after 3 min

Features	
Measuring Range	
Area, Volume Calculations	
Indirect measurement using Pythagoras	
Addition/Subtraction	
Continuous Measurement	
Min/Max Distance Tracking	
Display illumination and multi-line display.	
Buzzer indication	
The LDM-H series enhanced the measurement ability of outdoor application	
1.5±mm High Accuracy	

Size(HxWxD): 115 mm x 48 mm x 28 mm

Weight: 135 g

Accessories:

2 x 1.5V AAA batteries and gift box with carrying case.