3 PHASE ROTATION TESTER

Model: RT-616 *ISO-9001, CE, IEC1010*











The Art of Measurement

LCD display

3 PHASE ROTATION TESTER

Model: RT-616

FEATURES

- * Electronic (not mechanical) rotation test, high reliability.
- * LCD display, easy ready and simple operation.
- * Signal input voltage: 100V AC up to 660V AC max.

GENERAL SPECIFICATIONS

GENERAL SPECIFICATIONS						
Signal Input	100V AC up to 660 AC maximum,					
Voltage	3 min. limit for over 500V AC.					
Signal Current	Approx. 7 mA per phase.					
Consumption						
Signal Freq.	45 to 70 Hz.					
Range						
Circuit	* Electronic (not mechanical).					
	* Custom one-chip of microprocessor					
	LSI circuit.					
Power Supply	DC 9V battery. 006P, MN1604 (PP3)					
	or equivalent. Approx.					
Power	Approx. DC 8 mA.					
Consumption						
Operating	0 to 50 $^{\circ}\mathrm{C}$ (32 to 122 $^{\circ}\mathrm{F}$).					
Temperature						
Operating	Less than 80% RH.					
Humidity						
Dimension	100 x 50 x 25 mm.					
	3.9 x 1.9 x 1.0 inch.					
Weight	150 g/0.33 lb.					
Standard	* Operational manual1 PC					
Accessories	* Meter with 3 PCs 40 cm length					
	test lead and banana Plug1 SET					
	* Alligator clip3 PC					

Clockwise (correct)									
L1 L2 L3 R CORRECT									
Counter clockwise (correct)									
L1 L2 L3									
L L									
	FALSE	Ī							
Line is no connection (Incorrect)									
L1 missing	L1 missing				L2 missing				
L2	L3			L1		L3			
L1 MIS	SSING			L2	MISS	SING			
L3 missing			L1, L2, L3 missing						
L1 L2									
L3 MIS	SSING		L1L2L3 MISSING						

^{*} Appearance and specifications listed in this brochure are subject to change without notice.

0909-RT616