

# LIGHT TRANSMITTER

Model : TR-LXT1A4

ISO-9001, CE, IEC1010



**NDTKALA<sup>®</sup>.CO**  
Non-Destructive Test (NDT) Equipment

تامین تجهیزات و مواد مصرفی تست های غیر مخرب ایران  
۰۲۱-۷۱۰۵۳۸۸۸ | ۰۹۱۲۰۲۶۶۲۷۰



**Lutron**

**LUTRON ELECTRONIC**

***The Art of Measurement***

# LIGHT TRANSMITTER

Model : TR-LXT1A4

<b>Measure Range</b>	<p><i>Range 1 :</i> 0-2,000 Lux</p> <p><i>Range 2:</i> 2,000-20,000 Lux</p> <p><i>Range 3 :</i> 20,000-50,000 Lux</p>
<b>Output</b>	<p>4 - 20 mA</p> <p><i>Range 1 :</i> 0 Lux = 4 mA 1,000 Lux = 12mA 2,000 Lux = 20 mA</p> <p><i>Range 2:</i> 0 Lux = 4 mA 2,000 Lux = 5.6mA 20,000 Lux = 20mA</p> <p><i>Range 3 :</i> 0 Lux = 4 mA 20,000 Lux = 10.4 mA 50,000 Lux = 20 mA</p>
<b>External Adjustment</b>	ZERO VR SPAN VR
<b>Power Supply</b>	90 - 260 ACV 50 Hz/60 Hz
<b>Operation Temperature</b>	0 - 50 °C 32 - 122 °F
<b>Operation Humidity</b>	Less than 80 %RH
<b>Accessory Included</b>	Light probe
<b>Mounting</b>	Din rail or Wall Wall
<b>Case</b>	ABS plastic
<b>Others</b>	Separate probe with plug

\* Appearance and specifications listed in this brochure are subject to change without notice.