

SOUND TRANSMITTER

Model : TR-SLT1A4

ISO-9001, CE, IEC1010



4-20 mA Controller/Alarm/Indicator
Model : CT-2012



Lutron



www.YaLAB.com.tw

The Art of Measurement

SOUND LEVEL TRANSMITTER

Model : TR-SLT1A4

Measure Range	Range 1: 30 - 80 dB Range 2: 50 - 100 dB Range 3: 80 - 130 dB
Output	4 - 20 mA Range 1: 30 dB:7.69 mA 80 dB:13.84mA Range 2: 50dB:10.15 mA 100dB:16.3mA Range 3: 80dB:13.84mA 130 dB:20 mA
External Adjustment	94 dB Cal. VR
Power Supply	90 - 260 ACV 50 Hz/60 Hz
Operation Temperature	0 - 50 °C 32 - 122 °F
Operation Humidity	Less than 80 %RH
Accessory Included	Sound level Probe
Optional Accessories	Sound calibrator SC-941 (94 dB) SC-942 (94 dB/114 dB)
Mounting	Din rail or Wall
Case	ABS plastic
Others	Separate probe

* Appearance and specifications listed in this brochure are subject to change without notice.

TR-SLT1A4+1608

www.YaLAB.com.tw 02-2389-0101