

DIGITAL ANEMOMETER
MS6252A / MS6252B



Specifications		MS6252A	MS6252B
Specifications	Range	Accuracy	
m/s (meter per second)	0.80~30.00 m/s	±(2.0%+50)	
	30.00~40.00 m/s	For Reference only	
km/h (kilometer per hour)	1.40~108.00 km/h	±(2.0%+50)	
	108.00~144.00 km/h	For Reference only	
ft/s (feet per second)	1.30~98.50 ft/s	±(2.0%+50)	
	98.50~131.20 ft/s	For Reference only	
Knots (nautical miles per hour)	0.80~58.30 knots	±(2.0%+50)	
	58.30~77.70 knots	For Reference only	
mile/h (mile per hour)	0.90~67.20 mil/h	±(2.0%+50)	
	67.20~90.00 mil/h	For Reference only	
ft/m (feet per minute)	78~5900 ft/m	±(2.0%+50)	
	5900~7874 ft/m	For Reference only	
Air Volume Unit	CFM	0~9.9990ft ³	
	CMM	0~9.9990m ³	
	CMS	0~9.999m ³	
Temperature	-20~60°C	±1.5°C	
	-4~140°F	±2.7°F	
Relative Humidity	(20~80%) RH	±3%	
	(<20~>80%) RH	±5%	
Features			
Display	counts	9999	9999
APO	Auto Power Off	●	●
Flow Area Setting		●	●
MAX/MIN		●	●
°C/°F Selection		●	●
Data Hold		●	●
Ambient			●
Dew Point			●
Wet Bulb			●
Temperature			●
Display Backlight		●	●
LBD	Low Battery Display	●	●
USB Interface	(Windows OS)		●
General			
Power Supply	1×9V 6F22 Battery		
Product Size	165mm×85mm×38mm/6.5"×3.3"×1.5"		
Product Weight	168g/0.37lb		
Safety Rating	CE RoHS		

● Feature Difference



MS6252A

CFM	99990	9.9990ft ³
CMM	99990	9.9990m ³
CMS	9999	9.999m ³
m/s	km/h	ft/s
knots	mile/h	ft/m
CFM	CMM	CMS
Apo	MAX MIN	☐
☐	☐	☐



MS6252B

CFM	99990	9.9990ft ³
CMM	99990	9.9990m ³
CMS	9999	9.999m ³
m/s	km/h	ft/s
knots	mile/h	ft/m
CFM	CMM	CMS
☐	DP	WB
°F/°C	☐	USB
Apo	MAX MIN	☐
☐	☐	☐

กรุณาติดต่อ
บริษัท เน็ โอนิกส์ จำกัด
โทร 02-077-7602 หรือ 061-8268939
E-mail:sale@neonics.co.th

LINE ID:neonicstool

