HABOTEST®

Digital Clamp Meter True RMS

HT206B

1. AC/DC Voltage
2. AC Current
3. Resistance
4. Capacitance
5. Frequency
6. Diode Test
7. Continuity Test
8. NCV

NDTKALA.co
Non-Destructive Test (NDT) Equipment
تامین تجهیزات و مواد مصرفی تست های غیر مخرب ایران
۰۹۱۲۰۲۴۶۲۷۰ ۰۲۱-۷۱۰۵۳۸۸۸

1. General Specifications

The new generation of high-performance digital clamp meter makes your work easier, more efficient and safer. Measurable AC/DC voltage, AC current, frequency, duty cycle, resistance, temperature, diode, continuity, NCV, etc.

2. Features

1. Made of high - quality materials, it is durable, very practical, wear - resistant and stable in performance. It features hold result and max value buttons that makes it quicker and easier to use.
2. A two - wire display that displays AC voltage / current and frequency or Celsius and Fahrenheit on the screen. LCD Display: Ultra -clear display, clear reading, easy to read the values when you operate.
3. Hold and backlight button:The data hold button and backlight button are on the side of the meter. A short press will hold the data for you, and a long press will turn the backlight on. It is convenient for one-handed operation when measuring.
4. Avoid hazardous situations by using the convenient clamp to safely measure AC currents without having to strip a cord or break a circuit.
5. Auto power off: no operation in 15 minutes. The instrument will shut down automatically to save battery energy.
6. Multifunctional: Accurate AC/DC voltage, AC current, frequency, duty cycle , capacitance , resistance , temperature , diode, continuity, NCV, etc.
7. Wide range of applications, ideal for home and professional use, automotive, home and industrial electrical troubleshooting.

3. Technical Specifications

AC Current	Range: 6A/60A/600A Accuracy: ±(2.5%+5)
DC Voltage	Range: 600mV/6V/60V/600V Accuracy: ±(0.5%+3)
AC Voltage	Range: 6V/60V/600V/600V Accuracy: ±(1.0%+3)
Resistance	Range: 600Ω/6kΩ/60kΩ/600kΩ/ 6MΩ/60MΩ Accuracy: ±(1.0%+3)
Capacitance	Range: 10nF/100nF/1μF/10μF/ 100μF/1mF/10mF/ 100mF Accuracy: ±(4.0%+3)
Frequency	Range: 10Hz/100Hz/1kHz/ 10kHz/100kHz/1MHz/ 10MHz Accuracy: ±(0.5%+5)
Duty	Range: 1%~99% Accuracy: ±(1.0%+2)
Temperature	Range: -40°C~1000°C Accuracy: ±(1.0%+2)
Counts	6000
Continuity	√ (sound and light alarm)
NCV	√ (sound and light alarm)
Display	LCD Display
Jaw Opening	25 cm
Power Supply	2 x AAA (1.5V) Batteries
Dimensions	193mmx 73 mm x 34 mm
Weight	260g

SPARTNA

Spartna General Trading L.L.C
+971547796588
info@spartna.com