



Honeywell

You are browsing the product catalog for

Germany



SINGLE GAS

Honeywell BW™ Solo

Honeywell BW™ Solo

Overview



Honeywell BW™ Solo is an easy to service single-gas detector with BLE connectivity that provides real-time visibility into the status and safety of hazardous-area workers, helping companies respond faster, more knowingly and decisively to safety incidents. Data from the detector or its docking station is downloadable to a PC, where it can be aggregated and managed through Honeywell's Safety Suite software platform to automate key compliance tasks like regulatory records management. Can detect up to 15 user-selected common and exotic gases. User-friendly operation, lightweight convenience and ease of maintenance and serviceability can lower long-term ownership cost of a gas monitoring system.

Features and Benefits:

- User-friendly operation
- Easy-to-read display for multiple languages
- Lightweight convenience



- Ease of maintenance
- Serviceability
- The new 1-Series sensor for enhanced reliability Connected Bluetooth Low Energy (BLE) capabilities Quick Specs:
- High standards of sensor quality and reliability
- The easiest single-gas detector to service
- The first single-gas detector with the 1 Series sensor for CO, H₂S, O₂, and CO₂
- Complete with an extensive selection of sensor options
- Compatible with Honeywell IntelliDoX

How VIDEOS:

- [Introduction](#)
- [Unboxing](#)
- [Calibration](#)
- [Accessing the Menu and Info Screen](#)
- [Bump Test](#)
- [Power On and Off](#)
- [Replace Battery and Battery Door](#)
- [Replace Sensor Filter](#)
- [Safety Suite Device Configurator](#)
- [Safety Suite Device Manager](#)
- [Sensor Replacement - 1 Series](#)
- [Sensor Replacement - 4 Series](#)
- [Zero Sensor](#)

Even the best products deserve expert maintenance!

Elevate your gas detectors' potential with Honeywell's expert maintenance services! Maximize uptime, eliminate costs, and ensure on-time, on-budget project completion.

[Explore our fixed, portable, and high-tech support services now!](#)

Specifications

OVERVIEW

Brand

- BW

Warranty

- 3 years for 1-Series sensors and 1-Series detectors (excluding battery)

DIMENSION & WEIGHT

Weight

- 116 gram
- 4.1 ounce av

TEMPERATURE

Maximum Temperature

maximum temperature

- 140 degree Fahrenheit
- 60 degree Celsius

FEATURES

Sub-Category

- Single-Gas

Alarm Type

- Audible, Visual, Vibrating

Datalogging

- Six months at 5 second intervals

Features & Benefits

- The easiest single-gas detector to service, with no need to take it apart to replace sensors, batteries and sensor filters. That means long life and low cost.

User Options

- Reset TWA, STEL and Peak readings

Wireless Technology

- BLE

DIMENSIONS & WEIGHT

Instrument Size

- 2.7 x 2.6 x 1.4 in. / 7.0 x 6.7x 3.6 cm

TECHNICAL SPECIFICATIONS

Sensor Range

- H2S (0-200ppm), CO (0-2000ppm), O2 (0-30%vol), Cl2 (0-50ppm), ClO2 (0-1ppm), ETO (0-100ppm), H2 (0-1000ppm), HCN (0-100ppm), NH3 (0-1000ppm), NO (0-250ppm), NO2 (0-100ppm), O3 (0-1ppm), PH3 (0-5ppm), SO2 (0-100ppm)

Humidity Range

- 5%-95%

Gas Type

- H2S, CO, O2, Cl2, ClO2, ETO, H2, HCN, NH3, NO, NO2, O3, PH3, SO2

BATTERY & CHARGING

Battery Run Time

- 6-12

STANDARDS & CERTIFICATIONS

Standards

- Class I, Division 1, Groups A, B, C, D, T4

Ingress Protection

- IP68

OTHERS

Industry

- Energy



Please sign in to view part numbers available for purchase based on your account

[Sign In](#)

Search

Part Number	BWS-SK1
Description	BW SOLO REPLACEMENT SCREW KIT (25)
	SIGN IN

Rows 10

[Previous](#) [1](#) [Next](#)

Product Number



Please sign in to view part numbers available for purchase based on your account

[Sign In](#)

BWS-SK1

BW SOLO REPLACEMENT SCREW KIT (25)

BWS-SK1

BW SOLO REPLACEMENT SCREW KIT (25)

Alternative Products



ToxiRAE Pro CO2

Personal wireless carbon dioxide monitor





ToxiRAE Pro

Wireless single-gas and oxygen detector with interchangeable sensors



Honeywell BW™ Ultra

Honeywell BW™ Ultra

Honeywell
Industrial Automation
855 S Mint St
Charlotte, NC 28202
800-582-4263

Product name
© Current year Honeywell International Inc.
All rights reserved.

Honeywell

This document was generated on (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.

