

Intrinsically Safe Polymer Dual-Light

Flashlight



Floodlight



Dual-Light



120 Flashlight
Lumens

120 Floodlight
Lumens

- cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible for use in both above and below ground hazardous locations where explosive gases and dusts may be present.
- Flashlight/floodlight/dual-light
- Beam distance rated at 170 meters
- Engineered polymer housing



These non-rechargeable dual-lights are cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible for use in both above and below ground hazardous locations where explosive gases and dusts may be present. They each use a CREE® LED rated at 120 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 170 meters. A 120 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally both the flashlight and the floodlight can be turned on at the same time for maximum versatility. The dual body switches provide momentary or constant-on functionality for the flashlight and on/off functionality for the floodlight. Power comes from 3 AA batteries (not included).

INTRINSICALLY SAFE



XPP-5422G

XPP-5422B



NDTKALA®.CO
Non-Destructive Test (NDT) Equipment



تأمین تجهیزات و مواد مصرفی تست های غیر مخرب ایران
۰۲۱-۷۱۰۵۳۸۸۸ ۰۹۱۲۰۲۴۶۲۷۰

XPP 5420 series



Intrinsically Safe Polymer Dual-Light



XPP-5422G




XPP-5422B

SPECIFICATIONS

- Flashlight – floodlight – dual-light
- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant on flashlight
- Sharp focused beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-light (flashlight & floodlight at same time) for maximum versatility
- Engineered polymer housing
- Non-slip grip
- Dual body switches
- Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Includes removable lanyard
- Requires 3 AA batteries (not included)
- Available in black & green
- Limited Lifetime Warranty*

- Lumens: flashlight-120, floodlight-120, dual-light-240
- Run-time: flashlight-17.5 hrs, floodlight-17.5 hrs, dual-light-4.5 hrs
- Beam distance: 170 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 7in, head diameter: 1.8in, handle diameter: 1.5 x 1.1in, weight: 6.9oz

**INCLUDED**

- Flashlight with built-in pocket/belt clip
- Removable lanyard

SAFETY RATING

cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe
Permissible for use in both above and below ground hazardous
locations where explosive gases and dusts may be present

Patent 7,738,229



Built in pocket/belt clip



Dual body switches



Wide-beam floodlight



Bayco Products, Inc.

Permissible Nightstick 5422 Flashlight/Floodlight



APPROVAL No. 20-A130001-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS:

- 1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EN91, and Energizer Type L91 batteries only.
- 2) Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types.
- 3) Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only.
- 4) The Model Nightstick 5422 must not be opened in areas where permissibility is required.



CLASS I DIV I GRPS A-D T3
CLASS II & III DIV I GRPS E-G T135C
CLASS I ZONE D AEx Ia IIC T3 Ga
CLASS I ZONE D Ex Ia IIC T3 Ga
● I M1 Ex Ia I Ma
● II I G Ex Ia IIC T3 Ga
Ex Ia I Ma
Ex Ia IIC T3 Ga
Intertek ITS 13 ATEX27
IECEx ETL 13.0026X
-20°C to Tamb +40°C
1.5V/Cell AA Alkaline

NDT KALA®.CO
Non-Destructive Test (NDT) Equipment



نامین تجهیزات و مواد مصرفی تست های غیر مخرب ایران
۰۹۱۲۰۲۴۶۲۷۰ | ۰۲۱-۷۱۰۵۳۸۸۸

Model	UPC 0 17398
XPP-5422G	80093 8
XPP-5422B	80094 5

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the lifetime of the original owner. Includes the LEDs, housing, lenses, electronics and switches. Batteries, normal wear and abuse are excluded.